


STANDARD PROFILES

ROLLER CHAIN PROFILES



REFERENCE	STEP	ISO	W	V	H	C	K	h	J	d	RAIL	Kg/m
LA - 44	3/8"	06 - B1	20	10	10	9.2	15	4.2	2.8	4	C 2010	0.290
LA - 45	1/2"	08 - B1	24	20	9	12.7	11	4.8	3.5	4.9	C 2405	0.145
LA - 46	5/8"	10 - B1	28	23	12	15.2	18	5.1	3.6	5.5	C 2812	0.200
LA - 47	3/4"	12 - B1	28	23	12	16.7	18	5.7	3.9	6.2	C 2812	0.200
LA - 48	1"	16 - B1	38	32.5	20	24.4	30	9.9	8.4	8.9	C 3818	0.770
LA - 48 - A	1" ¼	20 - B1	60	60	25	28.0	35	11.9	10.0	11	C 6020	1.040
LA - 48 - B	1" ½	24 - B1	60	60	30	35.0	40	14.9	13.0	16	C 6020	1.340
LA - 48 - C	1" ¾	28 - B1	60	65	40	39.0	45	18.0	16.0	17	C 6020	1.840
LA - 48 - D	2"	32 - B1	60	70	40	44.0	45	21.7	16.0	19	C 6020	2.040