

HIGH-PERFORMANCE PLASTICS

DELIVERY PROGRAM

ROUND RODS

DIAMETER (mm)		RANCES nm)	KG/ METER	PVDF 1000				
Standard length 3000 mm								
10	+0.1	+0.7	0.15	•				
12	+0.2	+0.8	0.22	•				
15			0.34	•				
20			0.60	•				
25	+0.2	+1.0	0.93	•				
30	+0.2	+1.1	1.34	•				
35	+0.2	+1.2	1.82	•				
40			2.37	•				
45	+0.3	+1.3	2.99	•				
50			3.74	•				
56	+0.3	+1.6	4.58	•				
60			5.35	•				
70			7.25	•				
80	+0.4	+2.0	9.35	•				
90	+0.5	+2.2	11.90	•				
95	+0.6	+2.5	13.77	•				
100			14.80	•				
110	+0.7	+3.0	17.86	•				
125	+0.8	+3.5	22.94	•				
Standard length 1000 mm								
140	+0.9	+3.8	28.92	•				
150	+1.0	+4.2	33.08	•				
165	+1.2	+5.0	39.87	•				
180	+1.2		47.57	•				
200	+1.3	+5.5	59.58	•				
225	+1.5	+6.2	77.25	•				
250			91.55	•				

Average production weights

PLATES

THICKNESS (mm)	TOLERANCES (mm)		KG/ METER	PVDF 1000			
Standard size 610 x 1000 mm							
10	+0.2	+1.1	13.07	•			
12	+0.3	+1.5	15.13	•			
16			19.81	•			
20			24.51	•			
22			26.97	•			
25			30.39	•			
30	+0.5	+2.5	36.95	•			
35			43.10	•			
40			48.67	•			
45			54.76	•			
50			60.41	•			
60	-0.5	+3.5	72.71	•			
80			96.38	•			
Other standard sizes 1000 x 1000 mm							

Average production weights