



BARRAS REDONDAS

DIÁMETRO (mm)	TOLERANCIAS (mm)		KG/METRO	STOCK
Longitud estándar 3000 mm				
10	+0.1	+0.7	0.15	●
12			0.22	●
15			0.34	●
20			0.60	●
25	+0.2	+1.0	0.93	●
30	+0.2	+1.1	1.34	●
35	+0.2	+1.2	1.82	●
40	+0.3	+1.3	2.37	●
45			2.99	●
50			3.74	●
56			4.58	●
60	+0.3	+1.6	5.35	●
70	+0.4	+2.0	7.25	●
80			9.35	●
90			11.90	●
95			13.77	●
100	+0.6	+2.5	14.80	●
110	+0.7	+3.0	17.86	●
125	+0.8	+3.5	22.94	●
Longitud estándar 1000 mm				
140	+0.9	+3.8	28.92	●
150	+1.0	+4.2	33.08	●
165	+1.2	+5.0	39.87	●
180			47.57	●
200	+1.3	+5.5	59.58	●
225	+1.5	+6.2	77.25	●
250			91.55	●

Pesos medios de producción

PLACAS

ESPESOR (mm)	TOLERANCIAS (mm)		KG/ METRO	STOCK
Tamaño estándar 610 x 1000 mm				
10	+0.2	+1.1	13.07	🟢
12	+0.3	+1.5	15.13	🔴
16			19.81	🟢
20			24.51	🟢
22			26.97	🟢
25			30.39	🟢
30			36.95	🟢
35	+0.5	+2.5	43.10	🟢
40			48.67	🟢
45			54.76	🟢
50			60.41	🟢
60	-0.5	+3.5	72.71	🟢
80			96.38	🟢

Otros tamaños estándar 1000 x 1000 mm

Pesos medios de producción

● Estándar: normalmente en stock
● Semi estándar: normalmente no disponible en stock
○ No estándar: normalmente no disponible en stock, producido por encargo y sujeto a condiciones especiales