



BARRAS REDONDAS

DIÂMETRO (mm)	TOLERÂNCIAS (mm)		KG/METRO	PVDF 1000
Comprimento standard 3000 mm				
10	+0.1	+0.7	0.15	●
12			0.22	○
15	+0.2	+0.8	0.34	○
20			0.60	○
25	+0.2	+1.0	0.93	●
30	+0.2	+1.1	1.34	○
35	+0.2	+1.2	1.82	●
40			2.37	○
45			2.99	○
50	+0.3	+1.3	3.74	○
56			4.58	○
60	+0.3	+1.6	5.35	●
70			7.25	○
80	+0.4	+2.0	9.35	●
90	+0.5	+2.2	11.90	○
95			13.77	○
100	+0.6	+2.5	14.80	○
110	+0.7	+3.0	17.86	○
125	+0.8	+3.5	22.94	○
Comprimento standard 1000 mm				
140	+0.9	+3.8	28.92	○
150	+1.0	+4.2	33.08	○
165			39.87	○
180	+1.2	+5.0	47.57	○
200	+1.3	+5.5	59.58	○
225			77.25	○
250	+1.5	+6.2	91.55	○

Pesos médios de produção.

PLACAS

ESPESSURA (mm)	TOLERÂNCIAS (mm)		KG/METRO	PVDF 1000
Tamanho standard 610 x 1000 mm				
10	+0.2	+1.1	13.07	○
12			15.13	●
16			19.81	○
20	+0.3	+1.5	24.51	○
22			26.97	○
25			30.39	○
30			36.95	○
35			43.10	○
40	+0.5	+2.5	48.67	○
45			54.76	○
50			60.41	○
60			72.71	○
80	-0.5	+3.5	96.38	○
Outros tamanhos standard 1000 x 1000 mm				

Pesos médios de produção.