



## ROUND RODS

DIAMETER (mm) <sup>(1)(2)</sup>	STANDARD LENGTH	SEMITRON® ESd 410C	
		KG/PIECE <sup>(3)</sup>	STOCK
9.53	305	0.03	○
12.70	305	0.05	○
15.88	305	0.09	○
19.05	305	0.12	○
25.40	305	0.22	○
31.75	305	0.34	○
38.10	305	0.49	○
47.63	203	0.77	○
76.20	153	1.34	○
111.13	153	2.34	○

(1): all dimensions shown correspond to minimum values  
(2): for intermediate diameters not listed, please consult us  
(3): theoretical weights, based on nominal dimensions and mean density

## PLATES

THICKNESS (mm) <sup>(1)(2)</sup>	SEMITRON® ESd 410C		SEMITRON® ESd 500 HR		SEMITRON® ESd 520 HR	
	KG/PIECE <sup>(3)</sup>	STOCK	KG/PIECE <sup>(3)</sup>	STOCK	KG/PIECE <sup>(3)</sup>	STOCK
Standard size 305 x 305 mm <sup>(1)</sup>						
9.53	1.25	○	2.02	○	1.68	○
12.70	1.97	●	2.70	○	1.87	○
15.88	2.08	○	3.38	○	2.33	○
19.05	2.50	○	4.05	○	2.80	●
25.40	3.33	●	5.40	○	3.73	○
31.75	4.16	○	6.76	○	4.95	○
38.10	5.00	○	8.11	○	5.60	●
44.45	5.83	●	9.46	○	-	-
50.80	6.66	○	10.80	○	-	-
Standard size 305 x 610 mm <sup>(1)</sup>						
9.53	2.50	●	-	-	-	-
12.70	3.79	●	-	-	-	-
15.88	4.17	○	-	-	-	-
19.05	5.00	○	-	-	-	-
25.40	6.66	○	-	-	-	-

(1): all dimensions shown correspond to minimum values  
(2): for intermediate thicknesses not listed, please consult us  
(3): theoretical weights, based on nominal dimensions and mean density